

WPS-FH1

- ★ Camera pixels: 1920*1080
- ★ One-touch video/audio recording and image capture
- ★ Support max 256GB SD card or USB stick
- ★ Built-in 512Hz transmitter
- ★ Cable M/FT counter and Text
- ★ Zoom function (8 levels)
- ★ RCA CVBS input; HDMI/RCA video output
- ★ 4-hour battery life
- ★ Storage box for the accessories



Accessories

C23FH 	Camera size: $\varnothing 23\text{mm} \times 135\text{mm}$ Camera pixels: 1920*1080 Sensor size: 1/3" inch CMOS View angle: 105° Leds: 12pcs Waterproof: IP68 Skids: 40/80mm Lens material: Sapphire glass Suitable pipe diameter: 30-200mm Built-in 512Hz transmitter	K-FH1 	10.1 inch HD LCD screen: 345*175*54mm Total pixels: 1024*600 Storage medium: 64GB SD card & USB stick Video format: AVI Battery: 6000mAh 12V Running time: 4 hours 8 levels digital zoom M/FT switch and Count reset RCA CVBS input; HDMI/RCA video output
X-FH1 	Cable size: $\varnothing 332 \times 59\text{mm}$ Cable length: 30m Cable diameter: $\varnothing 6.3\text{mm}$, 4-core coaxial Counter Easy coil replacement	CH 	Input: AC100-240V~50/60Hz Output: DC 13.5V/5A Plug diameter: 2.1mm
Optional C25FH  Self leveling			

WPS-FH1-C28PT

- ★ Camera pixels: 1280*720
- ★ One-touch video/audio recording and image capture
- ★ Support max 256GB SD card or USB stick
- ★ Built-in 512Hz transmitter

- ★ Cable M/FT counter and Text
- ★ Zoom function (8 levels)
- ★ RCA CVBS input, RCA video output
- ★ 4-hour battery life
- ★ Storage box for the accessories



Accessories

C28PT 	Camera size: ø28mm*290mm Camera pixels: 1280*720 Sensor size: 1/4 inch CMOS View angle: 90° Leds: 2pcs Rotate: Pan 360°; Tilt 180° Waterproof: IP68 Skid: 40/90mm Built-in 512Hz transmitter	K-FH1-C28PT 	10.1 inch HD LCD screen: 345*175*54mm Total pixels: 1280*800 Storage medium: 64GB SD card & USB stick Video format: AVI Battery: 6000mAh 12V Running time: 4 hours 8 levels digital zoom M/FT switch and Count reset HDMI output (HD interface) Interface: RCA CVBS input; RCA video output
X-FH1-C28PT 	Cable size: ø332*59mm Cable material: Glass fiber line Cable length: 20m Cable diameter: ø6.3mm, 4-core coaxial Counter	K-FH1A-C28PT 	Size: 505*419*180mm
Optional  Universal skid (80-180mm)			